

Mobil Super™ 1000 X1 15W-40
Mobil Passenger-Vehicle-Lube , South Africa
Premium Multigrade Passenger Vehicle Motor Oil

Product Description

Mobil Super™ 1000 x1 15W-40 is a premium conventional motor oil that provides long engine life.

Features and Benefits

Mobil Super 1000 products are industry proven so you can trust you will get the performance you want from your vehicle. Mobil Super 1000 x1 15W-40 provides:

- Excellent engine cleanliness
- Good high temperature protection
- Good wear protection

Applications

Mobil Super 1000 products have been formulated to be suitable for use in nearly all vehicles. ExxonMobil recommends Mobil Super 1000 x1 15W-40 for daily driving under normal conditions:

- Older engine technologies
- Gasoline and Diesel without Diesel Particulate Filters (DPF)
- Passenger cars, SUV's, light trucks and vans
- Highway cruising
- Normal operating conditions

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product has the following approvals:
VW 501 01
VW 505 00
This product is recommended for use in applications requiring:
API CF

This product is recommended for use in applications requiring:

MB 229.1

This product meets or exceeds the requirements of:

API SJ

API SL

API SM

API SN

API SN PLUS

API SP

ACEA A3/B3

Properties and Specifications

Property	
Grade	SAE 15W-40
Pour Point, °C, ASTM D97	-30
Viscosity Index, ASTM D2270	142
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14.9
Density @ 15.6 C, g/ml, ASTM D4052	0.869
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	109
Flash Point, Cleveland Open Cup, °C, ASTM D92	239

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2025

