



Mobil Super™ Everyday Protection C3 5W-30

Mobil Passenger-Vehicle-Lube , Ukraine

High Quality Engine Oil

Product Description

Mobil Super™ Everyday Protection C3 5W-30 is a high-quality engine oil that provides wear protection to ensure a long engine life for various types and ages of gasoline and diesel vehicles equipped with particulate filters or catalytic converters.

Features and Benefits

Mobil Super Everyday Protection C3 5W-30 is designed to help with:

- Wear protection
- Engine cleanliness and sludge prevention
- Engine cold start-up and high-temperature protection

Applications

Mobil Super™ Everyday Protection C3 5W-30 is suitable for:

- Vehicles requiring ACEA C3 engine oils1
- Gasoline and Diesel engines with exhaust gas after-treatment systems such as catalytic converters and/or Diesel Particulate Filters (DPF)
- Passenger cars, SUV's, light trucks and vans operating under normal to occasionally severe conditions2

Notes

1: Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product meets or exceeds the requirements of:
ACEA C3
API SN
API SN PLUS

Properties and Specifications

Property	
Grade	SAE 5W-30

Property	
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	73.8
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	12.3
Density @ 15.6 C, g/ml, ASTM D4052	0.853
Pour Point, °C, ASTM D97	-27
Flash Point, Cleveland Open Cup, °C, ASTM D92	238
Viscosity Index, ASTM D2270	162

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2025

.

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved