



**Mobil ATF™ LT 71141**

Mobil Passenger-Vehicle-Lube , Denmark

Automatic Transmission Fluid

**Product Description**

Mobil ATF LT71141 is a high performance ATF with long drain-performance to be applied in automatic vehicle gearboxes.

**Features and Benefits**

Excellent cold properties.

Balanced additive performance ensuring a smooth transmission.

**Applications**

Mobil ATF LT71141 is designed to meet the specific requirements of automatic transmissions.

Mobil ATF LT71141 is used for the AL4 and 4HP20 gear boxes as the automatic transmission fluid.

**Specifications and Approvals**

| This product has the following approvals: |  |
|-------------------------------------------|--|
| PSA B71 2340                              |  |
| ZF TE-ML 04D                              |  |
| ZF TE-ML 11B                              |  |
| ZF TE-ML 14B                              |  |
| ZF TE-ML 17C                              |  |
| MB-Approval 236.11                        |  |
| DTFR 13C110                               |  |

| This product is recommended for use in applications requiring: |  |
|----------------------------------------------------------------|--|
| VW TL 52162                                                    |  |

**Properties and Specifications**

| Property                          |       |
|-----------------------------------|-------|
| Density @ 15 C, g/cm3, ASTM D4052 | 0.855 |

| Property                                      |      |
|-----------------------------------------------|------|
| Kinematic Viscosity @ 100 C, mm2/s, ASTM D445 | 7.4  |
| Kinematic Viscosity @ 40 C, mm2/s, ASTM D445  | 37.2 |
| Viscosity Index, ASTM D2270                   | 168  |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2024  
ExxonMobil Nordic  
Affiliate of ExxonMobil Nordic AS, Norway  
Gydevang 39-41  
DK-3450 Alleroed, Denmark  
Tel: +45 45 99 02 10  
Fax : +45 45 99 02 80  
[www.exxonmobil.no](http://www.exxonmobil.no)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)  
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved