



Gear Oil MB 317

Mobil passenger-vehicle-lube , Brazil

Transmission oil

Product Description

Gear Oil MB 317 is a premium synthetic blend manual transmission lubricant that is blended from high quality base oils and a high-performance additive system. This manual transmission fluid was developed for use in Mercedes-Benz Sprinter vans and A Class passenger vehicles. The product is approved against MB 235.10.

Features and Benefits

- Excellent thermal stability and oxidation resistance which extends gear and bearing life
- Wear protection which enables reliable load carrying while controlling maintenance costs
- Rust and corrosion protection to control wear under tough operating conditions
- Outstanding low temperature fluidity which reduces wear at start-up (SAE 80W-90)
- Excellent foam control which improves lubrication and extends seal life

Applications

Manual transmissions requiring a fluid approved against MB 235.10

Specifications and Approvals

This product has the following approvals:

MB-Approval 235.10

Properties and Specifications

Property	
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	7.3
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	37.8
Viscosity Index, ASTM D2270	162
Cold-Cranking Simulator, Apparent Viscosity @ -25 C, mPa.s, ASTM D5293	2210
Flash Point, °C, ASTM D92	238
Relative Density @ 15 C/15 C, ASTM D4052	0.86
Pour Point, °C, ASTM D97	-45

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2023

Cosan Lubrificantes e Especialidades S.A.

Praia da Ribeira, 01

21930-080 Rio de Janeiro – RJ - BRASIL

Tel: 0800 644 1562

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved